
ACU-RITE® DR0203


LCD Digital Readout Systems

A Tech Authority, Inc. 13745 Stockton Ave. Chino CA 91710 909-614-4522 sales@atechauthority.com



The most popular digital readout system in the machine tool marketplace, the DRO203 incorporates 7-inch color display technology with versatile software. Designed and manufactured in the USA, ACU-RITE readouts are the first choice of machine tool builders and users alike.








Dynamic zoom

The currently moving axis can be geographically highlighted. In "dynamic zoom" mode, the position value is zoomed to its maximum size depending on the number of digits. This greatly improves legibility—especially from a great distance.



Installation guide

When you switch on the digital readout for the first time, the DRO203 supports you with an installation guide. You are led step by step through the most important settings until the device is ready for operation.



Day/night switching

Depending on the ambient-light conditions at the machine, you can switch the screen of the DRO203 to a light or dark background.

	DRO203 Technical Data	
Display	• 3 Axes • 7-inch color wide screen (15:9)	
Common Functions	 Job Clock / Stop Watch Feed Rate Display Multiple Language Support Absolute/Incremental Near-Zero Warning with Graphics Help Function 	 16 Tool Offsets/Diameter Preset and Zero Reset 4 Function Calculator/Trig Calculator Instant Inch/mm Conversion Position-Trac™ Home Reference System Linear/Non-Linear Compensation up to ±9,999 ppm
Milling Specific Functions	 Bolt-hole Pattern Calculations with Graphics (full and partial circles/linear patterns) Centerline Calculation establish workpiece zero and midpoints 	Position X
Turning Specific Functions	 Lock Axis Feature establish tool offsets with the tool under load, resulting in reduced tool deflection. Instant radius / diameter conversion Taper calculator Vectoring 	Dio Taper Calculator Position
Options	Single-Position Tilting Base, Multiposition Holder, Mounting Frame, Protective Cover	
Construction	Die-Cast Metal	
Weight	~1.9 kg	
Data Interface	USB 2.0 type C • For Output of Parameters to a USB Stick or PC • For Input of Parameters, Remote Control of Keys and Commands	
Electrical Requirements	AC 100 V to 240 V (±10 %), 50 Hz to 60 Hz (±5 %), ≤ 33 W	
Operating Temperature	0° to 45° C (32° to 113° F)	
Storage Temperature	-20° to 70° C (-22° to 158° F)	
Protection EN60529	IP 40, Front Panel IP 54	

Mounting

The DRO203 can be flexibly positioned with the single-position tilting base. The multiposition holder and the mounting frame are suitable for mounting on the machine.





Multiposition Holder



SALES & SERVICE:

A Tech Authority, Inc. 13745 Stockton Ave. Chino CA 91710 909-614-4522 sales@atechauthority.com





HEIDENHAIN CORPORATION

333 East State Parkway Schaumburg, IL 60173-5337 USA

® (847) 490-1191

(847) 490-3931

www.acu-rite.com